

18-24-12 with PCSCU

- **Contains NS-54™ coated slow release nitrogen to provide uniform growth with extended nitrogen feeding.**
- **SGN215 for use on fairways, roughs and other turf areas.**

GUARANTEED ANALYSIS

Total Nitrogen (N).....	18.00%
9.40% Ammoniacal Nitrogen	
8.60% Urea Nitrogen*	
Available Phosphate (P ₂ O ₅)	24.00%
Soluble Potash (K ₂ O)	12.00%

Plant nutrients derived from diammonium phosphate, potassium chloride and polymer coated sulfur coated urea.

*8.60% Slowly Available Nitrogen from Polymer Coated Sulfur Coated Urea

Chlorine (Cl) Max.	10.10%
-------------------------	--------

F292

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.regulatory-info-ap.com>.

GENERAL INFORMATION

The Andersons Professional Turf™ Products 18-24-12 provides grass with nitrogen, phosphorus and potash for maintaining strong, vigorous turf.

The nitrogen in this product is both readily and slowly available which makes this product excellent for applications throughout the growing season when the minimum soil temperatures are greater than 55°F to 60°F and not exceeding 85°F.

This product is dust free and free flowing. The uniform particle sizing assures easy and accurate applications.

WHEN AND HOW TO USE

In the spring, or as soon as weather and ground conditions permit, apply 4.16 to 5.60 pounds of this product per 1,000 square feet. Repeat every six to eight weeks throughout the growing season.

To ensure that you have the best possible fertilization program, use fertilizers in conjunction with a soil and tissue test program operated by a state certified laboratory familiar with the soils of your region. Cooperative extension agents can provide the names of recommended labs in your area.

Apply only as directed.

Recent research has shown that environmental buffers prevent pollutants from entering our natural water bodies. To help protect these natural resources, avoid applying product to sidewalks, driveways, roadways, and other impervious surfaces. Sweep any misplaced granules back onto the area you are treating immediately after application, since storm drains often empty directly to nearby waterways.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of

product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS. Use contrary to label directions is not permitted.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.
 Manufactured by:
 The Andersons Lawn Fertilizer Division, Inc.
 P. O. Box 119
 Maumee, OH 43537

NS-54 is a trademark of The Andersons, Inc.

Suggested Spreader Settings

These suggested spreader settings are not intended to replace calibration.

Please calibrate your spreader before applying product.

50 lbs. feeds 12,000 sq. ft. (0.28 acre) with 1.00 lbs. P₂O₅/1,000 sq. ft. at the LOW RATE
50 lbs. feeds 8,900 sq. ft. (0.20 acre) with 1.34 lbs. P₂O₅/1,000 sq. ft. at the MEDIUM RATE

SPREADER SETTINGS

SPREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS	
			LOW RATE 4.16 lbs./1000 sq. ft.	MEDIUM RATE 5.60 lbs./1000 sq. ft.
Andersons Model 2000 AccuPro 2000; (cone 3) Andersons 2000 SR / SR- 2000 (cone 3)	3 mph	10 feet	M 1/2	N 1/2
Scotts R-8A (cone 3)	3 mph	10 feet	L 1/2	M 1/2
LESCO020093 (.25)	3 mph	9 feet	F	G
LESCO705698 (.25)	3 mph	9 feet	14	16
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm)	4.5 mph	38 feet	6 1/4 II-C	7 1/4 II-C
Vicon (03 Series)	4.5 mph	34 feet	30	34

APT18850.1
APT18850.2B