



BULB DUST-R MODEL 1150 USER'S MANUAL

Safety Precautions

- Use the cap on the delivery tube when bulb duster is not in use.
- Do not fill the bulb with any liquid or gel.
- Remove top slowly and without squeezing the bulb.
- Do not transport the bulb duster without the cap in place.
- Direct dust or granules only at surfaces to be treated.
- Use only E.P.A. approved dusts and granular formulations.
- Follow label directions and wear recommended protection.
- Do not expose bulb to solvents or extreme heat.

Suggested Uses

This delivery system can be used to apply dust and granular formulations of pesticides. Application sites include exposed surfaces, cracks, crevices, structural voids, and rodent burrows and runways. Specialized tips and extensions are included to assist in placing dust or granules in pest harborages.

Before Starting

- Inside of the bulb should be dry and free of obstructions.
- The screw threads on the cap and the bulb should be free of obstructions.
- The application tip should be securely attached to the hole in the top.
- Inspect the application tips and extensions for cracks.

Operating Instructions

Filling Bulb

- Wear protective materials directed by the pesticide label.
- Maintain the bulb upright during filling and capping.
- Do not use more than 6 ounces of dust or granular insecticide in the bulb.
- Add the insecticide to the bulb with the aid of a funnel to prevent spilling.
- Hand tighten the cap on the bulb before application.

Remaining Dust or Granules

- Unused pesticide in the bulb should be removed prior to long-term storage of the Bulb DustR. Empty bulb contents into the original pesticide container.

Care and Maintenance

- Clean bulb with a nylon brush, and with soap and water.
- Inspect the cap and application tubes for cracks; inspect bulb for damage
- Replace bulb if damaged, and cap if it is cracked or broken.

Trouble Shooting

Problem: Dust leaking around the cap or application tips.

- Solution:**
- Hand-tighten the cap
 - Tighten the tip attachments
 - Replace cap (#22055651) if cracked or broken
 - Replace tip (#22058500) or plastic extensions (#95150905) if cracked.

Problem: Not enough dust or granules delivered.

- Solution:**
- Rotate the bulb to loosen the contents, tilt the bulb slightly forward
 - Add marble or bearing in bulb to reduce dust or granule clumping
 - Add more dust or granules to bulb

Problem: Too much dust or granules delivered.


- Solution:**
- Reduce the amount of pesticide in bulb

Problem: Leaking dust or granules from the bulb

- Solution:**
- Inspect bulb for damage producing cracks and leaks; replace bulb (#22055650)

Optional Identification Label

Inside the parts bag is an Optional Identification Label. You may want to apply this to help better identify the Dust Bulb in the field. It can be applied in the location shown (right). To obtain the best adhesion of this label, please clean the area with alcohol or a similar solution before placing label on the bulb.



135 REGION SOUTH DRIVE • JACKSON, GA 30233
Toll Free 800-544-8811 • Phone 678-688-5601
www.bgequip.com • Fax 678-688-5633