

TECHNICAL DATA SHEET

PRODUCT INFORMATION

NAME	Cyclone 3™
MODEL NUMBER	FZVAAJ-3
MSRP	\$269.99
UPC / BARCODE	850020839636



PRODUCT IMAGE



DESCRIPTION

Now introducing the 4-Gallon Cyclone Series 3 Sprayer! With a 25-ft spray distance, this sprayer introduces design updates that significantly improve your spraying experience. By taking our customers feedback, we've implemented various tank advancements and brand new nozzle lineups.

To view the most updated operation guide visit: www.fzspray.com/operation-guides or scan the OR code



WHAT'S INCLUDED	PART NUMBER		PART NUMBER
18/2.6Ah LI-ION BATTERY	FZAAEN	UV-RESISTANT 5-FT PVC HOSE	FZRAOF
21V/1A BATTERY CHARGER	FZAAEP	ADJUSTABLE CONE NOZZLE	FZAAOL
STAINLESS-STEEL WAND	FZRAAS	0° PIN STREAM TEEJET NOZZLE	FZAAOK
SPRAY GUN	FZRABV	45° FAN TEEJET NOZZLE	FZAANM
COMFORTSTRAPS™	FZAAGD		

LOGISTICAL INFORMATION						
GROSS / NET WEIGHT	14 / 12 pounds	PALLET QUANTITY	36 units			
PACKAGE SIZE	14" x 9.5" x 21.7"	20' GP QUANTITY	420 units			
WEIGHT PER UNIT	13 lbs	40' GP QUANTITY	840 units			
WEIGHT PER PALLET	591 lbs	40' HQ QUANTITY	1080 units			

AGENCY/STANDARDS

APPROVALS

PRODUCT SPECIFICATIONS							
TANK TYPE PUMP TYPE	4-Gallon Backpack Standard Pressure Diaphragm Pump (LR)		GUN / WAND TYPE	Pressure Washer Spray Gun with Viton™ Seal / Quick-Connect Stainless Steel Wand			
WORKING PRESSURE	Low Speed (open flow) 8 psi	flow) (dead head)	BATTERY VOLTAGE/CAPACITY	18V / 2.6Ah			
WORKINGT REGOORE			BATTERY CELL TYPE	Lithium Ion			
SEAL TYPE	Viton™		CHARGER TYPE	21V / 1A			
FLOW RATE	Low Speed (open flow) .25 GPM	High Speed (open flow) .50 GPM	CHARGE TIME	~2 hours			
LIQUID OUTPUT / CHARGE Low Speed (open flow) > 60 gal		(open flow) (open flow)	BATTERY CYCLE LIFE	1,000 Charge Cycles			
			CONTINUOUS WORKING TIME	Low Speed	High Speed		
SPRAY DISTANCE	> 25 Feet (8 Meters)			> 140 minutes	> 110 minutes		

UL/CE/RoHS