according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

#### **SECTION 1. IDENTIFICATION**

Product name : DELTADUST DP0,05

Product code : Article/SKU: 04191098 UVP: 05952247 Specification:

102000004846 EPA Registration No: 101563-6

Manufacturer or supplier's details

Company name of supplier : Environmental Science U.S. LLC.

Address : 5000 Centregreen Way, Suite 400

Cary NC 27513

Telephone : 1-800-331-2867

Emergency telephone : +1 703-741-5970

E-mail address : uscontact@envu.com

Recommended use of the chemical and restrictions on use

Recommended use : Insecticide

Restrictions on use : See product label for restrictions.

#### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Combustible dust

Carcinogenicity (Inhalation) : Category 1B

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

: Category 1 (Lungs)

#### GHS label elements

Hazard pictograms



Signal Word : Danger

Hazard Statements : May form combustible dust concentrations in air.

H350 May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure if inhaled.

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P280 Wear protective gloves, protective clothing, eye protection

and face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

#### Other hazards

Cutaneous sensations may occur, such as burning or stinging on the face and mucosae. However, these sensations cause no lesions and are of a transitory nature (max. 24 hours).

Dust contact with the eyes can lead to mechanical irritation.

Contact with dust can cause mechanical irritation or drying of the skin.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Dustable powder (DP)

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 90 - <= 100
Quartz	14808-60-7	>= 1 - < 5
Stearic acid	57-11-4	>= 1 - < 5

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap.

Get medical attention if symptoms occur.

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

In case of eye contact : If in eyes, rinse well with water.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

No symptoms known or expected. May cause cancer by inhalation.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

Contact with dust can cause mechanical irritation or drying of

the skin.

Dust contact with the eyes can lead to mechanical irritation.

This product contains a pyrethroid.

Pyrethroid poisoning should not be confused with carbamate

or organophosphate poisoning.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : There is no specific antidote available.

Treat symptomatically.

In case of ingestion gastric lavage should be considered in cases of significant ingestions only within the first 2 hours. However, the application of activated charcoal and sodium

sulphate is always advisable.

Appropriate supportive and symptomatic treatment as indica-

ted by the patient's condition is recommended.

#### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Avoid generating dust; fine dust dispersed in air in sufficient

concentrations, and in the presence of an ignition source is a

potential dust explosion hazard.

Do not use a solid water stream as it may scatter and spread

fire.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides Metal oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version Revision Date: SDS Number: Date of last issue: -

09/14/2023 11272993-00001 Date of first issue: 09/14/2023 1.0

Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

Evacuate area.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions Avoid release to the environment.

> Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for

containment and cleaning up

Sweep up or vacuum up spillage and collect in suitable con-

tainer for disposal.

Avoid dispersal of dust in the air (i.e., clearing dust surfaces

with compressed air).

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are relea-

sed into the atmosphere in sufficient concentration.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures Static electricity may accumulate and ignite suspended dust

causing an explosion.

Provide adequate precautions, such as electrical grounding

and bonding, or inert atmospheres.

: If sufficient ventilation is unavailable, use with local exhaust Local/Total ventilation

ventilation.

: Do not breathe dust. Advice on safe handling

Do not swallow.

Avoid contact with eyes.

Avoid prolonged or repeated contact with skin.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

Minimize dust generation and accumulation. Keep container closed when not in use. Keep away from heat and sources of ignition.

Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store locked up.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Self-reactive substances and mixtures

Organic peroxides

Explosives Gases

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

inert or nuisance dust 50 Million particles per cubic foot

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

15 mg/m<sup>3</sup>

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

5 mg/m<sup>3</sup>

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

15 Million particles per cubic foot

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

Dust, nuisance dust and par-

ticulates

10 mg/m<sup>3</sup>

Value type (Form of exposure): PEL (Total dust)

Basis: CAL PEL

5 mg/m³

Value type (Form of exposure): PEL (respirable dust fraction)

Basis: CAL PEL

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	TWA (total dust)	15 mg/m³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m³	OSHA Z-1
		TWA (Respirable)	5 mg/m³ (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m³ (Calcium car- bonate)	NIOSH REL
Quartz	14808-60-7	TWA (Respirable dust)	0.05 mg/m³	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m³ (Silica)	ACGIH
		TWA (Res- pirable dust)	0.05 mg/m³ (Silica)	NIOSH REL
		PEL (respir- able)	0.05 mg/m³	OSHA CARC
Stearic acid	57-11-4	TWA (Inhal- able particu- late matter)	10 mg/m³	ACGIH
		TWA (Respirable particulate matter)	3 mg/m³	ACGIH

### **Engineering measures**

Minimize workplace exposure concentrations.

Apply measures to prevent dust explosions.

Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). If sufficient ventilation is unavailable, use with local exhaust ventilation.

## Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazar-

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

> dous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate

protection.

Hand protection

Material Chemical-resistant gloves

Remarks Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks

and at the end of workday.

Wear the following personal protective equipment: Eye protection

Safety goggles

Skin and body protection Skin should be washed after contact.

If exposure to chemical is likely during typical use, provide Hygiene measures

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** powder

Color white

Odor characteristic, very faint

Odor Threshold No data available

pΗ No data available

Melting point/freezing point No data available

Initial boiling point and boiling : No data available

range

Flash point Not applicable

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

Evaporation rate : Not applicable

Flammability (solid, gas) : May form combustible dust concentrations in air.

Upper explosion limit / Upper

flammability limit

Not applicable

Lower explosion limit / Lower

flammability limit

Not applicable

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Density : No data available

Bulk density : ca. 888.999 kg/m³

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Minimum ignition energy : > 10 mJ

Particle size : No data available

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac- :

tions

May form combustible dust concentrations in air.

Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Avoid dust formation.

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: No hazardous decomposition products are known.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

Limestone:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Quartz:

Acute oral toxicity : LD50 (Rat): > 22,500 mg/kg

Stearic acid:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l

Exposure time: 1 h
Test atmosphere: vapor

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

Assessment: The substance or mixture has no acute dermal

toxicity

#### Skin corrosion/irritation

Not classified based on available information.

#### **Components:**

Limestone:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Quartz:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Stearic acid:

Species : Rabbit

Method : Patch Test 24 Hrs.
Result : No skin irritation

#### Serious eye damage/eye irritation

Not classified based on available information.

### **Components:**

Limestone:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Quartz:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Stearic acid:

Species : Rabbit

Result : No eye irritation

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

### Respiratory sensitization

Not classified based on available information.

#### **Components:**

#### Limestone:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Remarks : Based on data from similar materials

Stearic acid:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Remarks : Based on data from similar materials

### Germ cell mutagenicity

Not classified based on available information.

#### **Components:**

#### Limestone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Stearic acid:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

May cause cancer by inhalation.

**Product:** 

Carcinogenicity - Assess-

ment

Sufficient evidence of carcinogenicity in inhalation studies with

animals

**Components:** 

Quartz:

Species : Humans

Application Route : inhalation (dust/mist/fume)

Result : positive

Carcinogenicity - Assess-

: Positive evidence from human epidemiological studies (inhala-

ment tion)

IARC Group 1: Carcinogenic to humans

Quartz 14808-60-7

(Silica dust, crystalline)

OSHA specifically regulated carcinogen

Quartz 14808-60-7

(crystalline silica)

NTP Known to be human carcinogen

Quartz 14808-60-7

(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Not classified based on available information.

Components:

Limestone:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion
Method: OECD Test Guideline 422

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

Result: negative

Remarks: Based on data from similar materials

Stearic acid:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

#### STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

#### Components:

Quartz:

Routes of exposure : inhalation (dust/mist/fume)

Target Organs : Lungs

Assessment : Shown to produce significant health effects in animals at con-

centrations of 0.02 mg/l/6h/d or less.

#### Repeated dose toxicity

### **Components:**

Limestone:

Species : Rat

NOAEL : > 300 mg/kg
Application Route : Ingestion
Exposure time : 28 Days

Method : OECD Test Guideline 422

Remarks : Based on data from similar materials

Quartz:

Species : Humans LOAEL : 0.053 mg/m³ Application Route : Inhalation

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

Stearic acid:

Species : Rat

NOAEL : 1,000 mg/kg
Application Route : Ingestion
Exposure time : 42 Days

Method : OECD Test Guideline 422

Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

#### **Components:**

Limestone:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

LL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

: EL50 (Desmodesmus subspicatus (green algae)): > 14 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility.

Based on data from similar materials

EL10 (Desmodesmus subspicatus (green algae)): > 14 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility.

Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Quartz:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 508 mg/l

Exposure time: 96 h

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 731 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Stearic acid:

Toxicity to fish : LL50 (Leuciscus idus (Golden orfe)): > 10,000 mg/l

Exposure time: 48 h Method: DIN 38412

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 10 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

No toxicity at the limit of solubility.

Toxicity to algae/aquatic

plants

NOELR (Pseudokirchneriella subcapitata (green algae)): > 10

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

No toxicity at the limit of solubility.

EL50 (Pseudokirchneriella subcapitata (green algae)): > 1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

No toxicity at the limit of solubility.

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOELR (Daphnia magna (Water flea)): > 0.5 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

No toxicity at the limit of solubility.

Toxicity to microorganisms : EC10 (Pseudomonas putida): 883 mg/l

Exposure time: 18 h

#### Persistence and degradability

## **Components:**

Stearic acid:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 71 % Exposure time: 28 d

Method: OECD Test Guideline 301B

according to the OSHA Hazard Communication Standard



## DELTADUST DP0,05

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

### Bioaccumulative potential

Components:

Stearic acid:

Partition coefficient: n-

octanol/water

: log Pow: 8.23

Mobility in soil

No data available

Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues It is best to use all of the product in accordance with label

> directions. If it is necessary to dispose of unused product, please follow container label instructions and applicable local

guidelines.

Do not dispose of waste into sewer.

Contaminated packaging Follow advice on product label and/or leaflet.

Empty containers retain residue and can be dangerous.

Do not re-use empty containers.

### **SECTION 14. TRANSPORT INFORMATION**

#### **International Regulations**

**UNRTDG** 

**UN** number : UN 3077

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, Proper shipping name

N.O.S.

(Deltamethrin)

Class 9 Ш Packing group Labels 9 Environmentally hazardous yes

IATA-DGR

UN/ID No. UN 3077

Proper shipping name Environmentally hazardous substance, solid, n.o.s.

(Deltamethrin)

Class 9 Packing group Ш

Labels Miscellaneous 956

Packing instruction (cargo

aircraft)

Packing instruction (passen-

ger aircraft)

: 956

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

Environmentally hazardous : yes

**IMDG-Code** 

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Deltamethrin)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **Domestic regulation**

**49 CFR** 

UN/ID/NA number : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Deltamethrin)

Class : 9 Packing group : III

Labels : CLASS 9 ERG Code : 171

Marine pollutant : yes(Deltamethrin)

Remarks : Above applies only to containers over 119 gallons or 450 li-

ters.

Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Combustible dust

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**US State Regulations** 

Pennsylvania Right To Know

Limestone 1317-65-3 Quartz 14808-60-7

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Permissible Exposure Limits for Chemical Contaminants

Limestone 1317-65-3 Quartz 14808-60-7

California Regulated Carcinogens

Quartz 14808-60-7

Product Type : Insecticides, acaricides and products to control other arthro-

pods


Active substance : 0.05 %

Deltamethrin

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

09/14/2023 11272993-00001 Date of first issue: 09/14/2023 1.0

CAL PEL California permissible exposure limits for chemical contami-

nants (Title 8, Article 107)

NIOSH REL USA. NIOSH Recommended Exposure Limits

OSHA CARC OSHA Specifically Regulated Chemicals/Carcinogens

USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-OSHA Z-1

its for Air Contaminants

USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-OSHA Z-3

eral Dusts

ACGIH / TWA 8-hour, time-weighted average Permissible exposure limit CAL PEL / PEL

NIOSH REL / TWA Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA CARC / PEL Permissible exposure limit (PEL) 8-hour time weighted average OSHA Z-1 / TWA OSHA Z-3 / TWA 8-hour time weighted average

AllC - Australian Inventory of Industrial Chemicals: ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance: ELx - Loading rate associated with x% response: EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

compile the Material Safety Data Sheet

Sources of key data used to : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

according to the OSHA Hazard Communication Standard



## **DELTADUST DP0,05**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/14/2023 11272993-00001 Date of first issue: 09/14/2023

Revision Date : 09/14/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8