according to the OSHA Hazard Communication Standard



Suspend SC

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

SECTION 1. IDENTIFICATION

Product name : Suspend SC

Product code : Article/SKU: 85789260 UVP: 85373676 Specification:

102000032681

Manufacturer or supplier's details

Company name of supplier : Environmental Science U.S. LLC.

Address : 5000 Centregreen Way, Suite 400

Cary NC 27513

Telephone : 1-800-331-2867

Emergency telephone : +1 703-741-5970

E-mail address : uscontact@envu.com

Recommended use of the chemical and restrictions on use

Recommended use

Insecticide

Restrictions on use : See product label for restrictions.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Other hazards

Cutaneous sensations may occur, such as burning or stinging on the face and mucosae. However, these sensations cause no lesions and are of a transitory nature (max. 24 hours).

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Suspension concentrate (=flowable concentrate)(SC)

Components

Chemical name	CAS-No.	Concentration (% w/w)
Propylene glycol	57-55-6	>= 10 - < 20
Deltamethrin	52918-63-5	>= 1 - < 5
Silicon, amorphous	112945-52-5	>= 1 - < 5

according to the OSHA Hazard Communication Standard



Suspend SC

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

No symptoms known or expected. This product contains a pyrethroid.

Pyrethroid poisoning should not be confused with carbamate

or organophosphate poisoning.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : There is no specific antidote available.

Appropriate supportive and symptomatic treatment as indica-

ted by the patient's condition is recommended.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides
Bromine compounds
Nitrogen oxides (NOx)

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment : Wear self-contained breathing apparatus for firefighting if

according to the OSHA Hazard Communication Standard



Suspend SC

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

for fire-fighters necessary.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety

practice, based on the results of the workplace exposure as-

sessment

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Gases

according to the OSHA Hazard Communication Standard



Suspend SC

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propylene glycol	57-55-6	TWA	10 mg/m³	US WEEL
Silicon, amorphous	112945-52-5	TWA (Dust)	20 Million par- ticles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA	6 mg/m³ (Silica)	NIOSH REL

Engineering measures : Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where

concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate

protection.

Hand protection

Material : Nitrile rubber

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the pro-

duct. Change gloves often!

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Skin should be washed after contact.

according to the OSHA Hazard Communication Standard



Suspend SC

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : suspension

Color : white

Odor : characteristic

Odor Threshold : No data available

pH : <= 7 (73 °F / 23 °C)

Concentration: 100 %

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : ca. $1.05 \text{ g/cm}^3 (68 \text{ °F} / 20 \text{ °C})$

Solubility(ies)

Water solubility : immiscible

Partition coefficient: n- : Not applicable

according to the OSHA Hazard Communication Standard



Suspend SC

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

octanol/water

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : 1,200,000 - 1,800,000 mPa.s (77 °F / 25 °C)

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Minimum ignition energy : Not applicable

Particle size : $\leq 5 \mu m$

 $\leq 3 \mu m$

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion

Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : LD50 (Rat): > 15,000 mg/kg

according to the OSHA Hazard Communication Standard



Suspend SC

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

Acute inhalation toxicity : Acute toxicity estimate: 19.24 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Components:

Propylene glycol:

Acute oral toxicity : LD50 (Rat): 22,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 44.9 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Deltamethrin:

Acute oral toxicity : LD50 (Rat, female): 87 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0.6 mg/l

Exposure time: 6 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Silicon, amorphous:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

according to the OSHA Hazard Communication Standard



Suspend SC

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

Components:

Propylene glycol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Deltamethrin:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Silicon, amorphous:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Propylene glycol:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Deltamethrin:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Silicon, amorphous:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Propylene glycol:

Test Type : Maximization Test

according to the OSHA Hazard Communication Standard



Suspend SC

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

Routes of exposure : Skin contact Species : Guinea pig Result : negative

Deltamethrin:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Propylene glycol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Deltamethrin:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 473

Result: negative

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro) Method: OECD Test Guideline 482

Result: negative

Silicon, amorphous:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

according to the OSHA Hazard Communication Standard



Suspend SC

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Propylene glycol:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Deltamethrin:

Species : Rat Application Route : Ingestion

Method : OECD Test Guideline 453

Result : negative

Silicon, amorphous:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Remarks : Based on data from similar materials

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Propylene glycol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Mouse

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Mouse

Application Route: Ingestion

according to the OSHA Hazard Communication Standard



Suspend SC

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

Result: negative

Deltamethrin:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rabbit

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Silicon, amorphous:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Components:

Deltamethrin:

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Propylene glycol:

Species : Rat, male NOAEL : >= 1,700 mg/kg

Application Route : Ingestion Exposure time : 2 y

Deltamethrin:

Species : Dog
NOAEL : 1 mg/kg
LOAEL : 10 mg/kg
Application Route : Ingestion
Exposure time : 52 Weeks

Method : OECD Test Guideline 452

according to the OSHA Hazard Communication Standard



Suspend SC

Version SDS Number: Revision Date: Date of last issue: -

08/28/2023 11262156-00001 Date of first issue: 08/28/2023 1.0

Silicon, amorphous:

Species Rat NOAEL 1.3 mg/l

Application Route inhalation (dust/mist/fume)

: 13 Weeks Exposure time

Remarks Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Propylene glycol:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 40,613 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Ceriodaphnia dubia (water flea)): 18,340 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Skeletonema costatum (marine diatom)): 19,300 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Ceriodaphnia dubia (water flea)): 13,020 mg/l

Exposure time: 7 d

Toxicity to microorganisms NOEC (Pseudomonas putida): > 20,000 mg/l

Exposure time: 18 h

Deltamethrin:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 0.15 μg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Gammarus fasciatus (freshwater shrimp)): 0.0003 µg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

ErC50 (Chlorella vulgaris (Fresh water algae)): > 0.47 mg/l

Exposure time: 96 h

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 0.017 µg/l

Exposure time: 260 d

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.0041 µg/l

Exposure time: 21 d

according to the OSHA Hazard Communication Standard



Suspend SC

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

Toxicity to microorganisms : EC50 (activated sludge): > 0.3 mg/l

Exposure time: 3 h

Silicon, amorphous:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 10,000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 10,000

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): 10,000

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Persistence and degradability

Components:

Propylene glycol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 98.3 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Deltamethrin:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Bioaccumulative potential

Components:

Propylene glycol:

Partition coefficient: n- : log Pow: -1.07

octanol/water Method: Regulation (EC) No. 440/2008, Annex, A.8

according to the OSHA Hazard Communication Standard



Suspend SC

Version SDS Number: Date of last issue: -Revision Date:

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

Deltamethrin:

Bioaccumulation Species: Lepomis macrochirus (Bluegill sunfish)

Bioconcentration factor (BCF): 1,400

Partition coefficient: n-

octanol/water

log Pow: 6.4

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues It is best to use all of the product in accordance with label

directions. If it is necessary to dispose of unused product, please follow container label instructions and applicable local

quidelines.

Do not dispose of waste into sewer.

Contaminated packaging Follow advice on product label and/or leaflet.

Empty containers retain residue and can be dangerous.

Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Deltamethrin, 2-Bromo-2-nitro- 1,3-propanediol)

Class 9 Packing group Ш Labels 9 Environmentally hazardous yes

IATA-DGR

UN/ID No. UN 3082

Environmentally hazardous substance, liquid, n.o.s. Proper shipping name

(Deltamethrin, 2-Bromo-2-nitro- 1,3-propanediol)

9 Class Packing group Ш

Miscellaneous Labels

Packing instruction (cargo

aircraft)

Packing instruction (passen-

964

964

ger aircraft) Environmentally hazardous yes

14 / 17

according to the OSHA Hazard Communication Standard



Suspend SC

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Deltamethrin, 2-Bromo-2-nitro- 1,3-propanediol)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(Deltamethrin, 2-Bromo-2-nitro- 1,3-propanediol)

Class : 9 Packing group : III

Labels : CLASS 9 ERG Code : 171

Marine pollutant : yes(Deltamethrin, 2-Bromo-2-nitro- 1,3-propanediol)

Remarks : Above applies only to containers over 119 gallons or 450 li-

ters.

Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

according to the OSHA Hazard Communication Standard



Suspend SC

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

 Water
 7732-18-5

 Propylene glycol
 57-55-6

 Deltamethrin
 52918-63-5

 Silicon, amorphous
 112945-52-5

California Permissible Exposure Limits for Chemical Contaminants

Silicon, amorphous 112945-52-5

Product Type : Insecticides, acaricides and products to control other arthro-

pods


Active substance : 50 g/l

Deltamethrin

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA Z-3 / TWA : 8-hour time weighted average

according to the OSHA Hazard Communication Standard



Suspend SC

Version Revision Date: SDS Number: Date of last issue: -

1.0 08/28/2023 11262156-00001 Date of first issue: 08/28/2023

US WEEL / TWA : 8-hr TWA

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 08/28/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8