

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 454
IDENTITY: ERADICATOR MULTIPUR INSEC Revision Date: 11/03/2010

Section I

Manufacturer's Name:QUEST CHEMICAL CORPORATION Telephone Numbers:
Address: 12255 FM 529 Emergency:
NORTHWOODS INDUSTRIAL PARK 800/255-3924
HOUSTON Information:
State: TX Zip Code:77041 713/8968188

HMIS CODES: REACTIVITY: 0 FLAMMABILITY: 1 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %. Contains entries for ISOPARAFINIC HYDROCARBON and PROPANE/N-BUTANE.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: N/A Specific Gravity (water=1) 0.97
Vapor Pressure(mm Hg) <17 Melting Point: N/A
Vapor Density(AIR=1) >1 Evaporation Rate: <0.8
Solubility in Water: >61% (Butyl Acetate=1)
Appearance and Odor: MILKY, SLIGHT INSECTICIDAL ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point(Method Used):>200F TCC Flammable Limits: LEL:N/A UEL: N/A
Extinguishing Media: DRY CHEMICAL, CO2, FOAM, OR WATER SPRAY
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS IS
ALWAYS RECOMMENDED WHEN FIGHTING FIRES.

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO
TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE
ATMOSPHERE IN CONFINED AREAS.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 454

=====
Stability: Unstable: Conditions to avoid:
 Stable: X TEMPERATURES ABOVE 120 F, HOT SURFACES
Incompatibility (Materials to Avoid): STRONG OXIDIZERS, STRONG REDUCERS,
ALKALIES, AND ACIDS
Hazardous Decomposition or Byproducts: OXIDES OF CARBON UNDER FORCED
COMBUSTION
Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

=====
Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
EYES: MAY CAUSE IRRITATION. SKIN: MAY CAUSE REDDENING AND IRRITATION.
INHALATION: MAY CAUSE NASAL & RESPIRATORY IRRITATION, NAUSEA AND NERVOUS
SYSTEM DISORDERS. INGESTION: MAY CAUSE NAUSEA, CRAMPS AND VOMITING.
Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR AND
SEE PHYSICIAN. EYES: FLUSH WITH WATER AND SEE PHYSICIAN. SKIN: FLUSH WITH
WATER AND REMOVE CONTAMINATED CLOTHING AND WASH AFFECTED AREA WITH SOAP AND
WATER. INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

=====
Steps to be Taken in Case Material is Released or Spilled: MOP OR WIPE UP
SPILL. REMOVE SOURCES OF IGNITION. PREVENT SPILLED MATERIAL FROM ENTERING
WATERWAYS.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL,
STATE AND LOCAL GUIDELINES. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.
DO NOT PUNCTURE OR INCINERATE CONTAINER.

Precautions to be Taken in Handling and Storing: STORE IN A COOL DRY AREA.
KEEP AWAY FROM HEAT, FLAMES OR SPARKS. EXPOSURE TO TEMPERATURES >120 F MAY
CAUSE BURSTING.
Other Precautions: FOLLOW LABEL DIRECTIONS EXPLICITLY. VAPOR MAY COLLECT
IN LOW LYING AREAS.

Section VIII: CONTROL MEASURES

=====
Respiratory Protection: USE ONLY IN WELL VENTILATED AREA.
Ventilation: Local Exhaust:N/A
Mechanical: WHEN USING PRODUCT IN CONFI Special: N/A
Other: N/A
Protective Gloves:N/A
Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.
Other Protective Clothing or Equipment:
N/A
Work/Hygienic Practices:
WASH HANDS AFTER USE

□