

PRODUCT INFORMATION

NAME	Typhoon 2.5™
MODEL NUMBER	FZVAAK-2.5
MSRP	\$318.99
UPC / BARCODE	850020839254



PRODUCT IMAGE



DESCRIPTION

For the first time, the popular 4-gallon TYPHOON unit is equipped with an industry-leading five-setting variable pressure control dial. A crowd favorite, the Typhoon is a powerful tool capable of pressures up to 115 psi with a battery life of three hours.

To view the most updated operation guide visit: www.fzspray.com/operation-guides or scan the QR code



WHAT'S INCLUDED

	PART NUMBER	PART NUMBER
18/5.2Ah LI-ION BATTERY	FZAAEM	UV-RESISTANT 5-FT HOSE
21V/2.5A BATTERY CHARGER	FZAAEL	FZRAFL
STAINLESS-STEEL WAND	FZRAAS	ADJUSTABLE CONE NOZZLE
SPRAY GUN	FZRAAV	FZAAAR
COMFORTSTRAPS™	FZAAGD	0° PIN STREAM NOZZLE
		FZAAAP
		25° FAN NOZZLE
		FZAAAQ

LOGISTICAL INFORMATION

GROSS / NET WEIGHT	16 / 14 lbs	PALLET QUANTITY	36 units
PACKAGE SIZE	14" x 9.5" x 21.7"	20' GP QUANTITY	420 units
WEIGHT PER UNIT	16 lbs	40' GP QUANTITY	840 units
WEIGHT PER PALLET	627 lbs	40' HQ QUANTITY	1080 units

PRODUCT SPECIFICATIONS

TANK TYPE	4-Gallon Backpack		GUN / WAND TYPE	Pressure Washer Spray Gun with Viton™ Seal / Quick-Connect Stainless Steel Wand	
PUMP TYPE	Heavy-Duty Diaphragm Pump		BATTERY VOLTAGE/CAPACITY	18V / 5.2Ah	
WORKING PRESSURE	Low Speed (open flow) 7 psi	High Speed (dead head) 115 psi	BATTERY CELL TYPE	LG 18650 Lithium Ion	
SEAL TYPE	Viton™		CHARGER TYPE	21V / 2.5A	
FLOW RATE	Low Speed (open flow) .12 GPM	High Speed (open flow) 1.12 GPM	CHARGE TIME	~1 hour	
LIQUID OUTPUT / CHARGE	Low Speed (open flow) > 110 gal	High Speed (open flow) > 110 gal	BATTERY CYCLE LIFE	1,000 Charge Cycles	
SPRAY DISTANCE	> 30 Feet (10 Meters)		CONTINUOUS WORKING TIME	Low Speed > 180 minutes	High Speed > 120 minutes
			AGENCY/STANDARDS APPROVALS	UL / CE / RoHS	