

GHS Safety Data Sheet PROFILE Products, LLC

Slik Color™

MSDS Number: LIM029 Revision Date: 1/1/14

Page 1 of 4

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

PROFILE Products, LLC 750 LAKE COOK ROAD SUITE 440 BUFFALO GROVE, IL 60089

Phone: (847) 215-1144
Fax: (847) 215-0577
Email: profileproducts.com
Web: www.profileproducts.com

Product Name: Slik Color™
Revision Date: 1/1/14
MSDS Number: LIM029
Common Name: N.A.

Product Use: Erosion control mulch additive for hydraulic seeding.

Description: Proprietary blend of clay, anionic polyacrylamide polymer and dye crystals.

2 HAZARDS IDENTIFICATION

Inhalation: Lungs
Skin Contact: No

Ingestion: Toxic by ingestion- Do not induce vomitting.

Crystalline Silica (Quartz) [EPA Hazard Category: Health]

Carcinogen: OSHA - No NTP - Yes (respirable) IARC - Yes

This product contains up to 2.5% crystalline silica. The International Agency for Research on Cancer (IARC) has stated that there is sufficient evidence of carcinogenicity of crystalline silica to human beings. It was noted that carcinogenicity was not detected in all industrial circumstances studied. The NTP's Sixth Annual Report on Carcinogens include respirable crystalline silica. The Hazard Communication Standard (29CFR 1910.1200) requires that any material containing over 0.1% of a substance reported as a carcinogen in an IARC monograph or the most recent NTP Annual Report on Carcinogens must be identified as a carcinogen. These identifications are for hazard communications only and do not serve as assessments of carcinogenic risk. Crystalline silica is known to cause silicosis. At dust levels below the recommended PEL exposure to the crystalline silica contained in this product should not present a health hazard.

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Perc.	Chemical	Name
14808607	1.5-2.5%	Silica,	crystalline quartz



GHS Safety Data Sheet PROFILE Products, LLC

Slik Color™

MSDS Number: LIM029 Revision Date: 1/1/14

Page 2 of 4

569642 | <20% | C.I. Basic Green 4

FIRST AID MEASURES

Inhalation: Usually not a problem. Remove to fresh air if respiratory irritation develops, and get medical aid promptly if irritation

persists.

Skin Contact: Wash throughly with soap and water.

Eye Contact: Flush thoroughly with water. See a physician if discomfort persists. Do not wear contact lenses.

Ingestion: Do not induce vomitting. Get medical attention immediately.

5 FIRE FIGHTING MEASURES

Non-flammable and non-hazardous Use water, carbon dioxide foam.

6 ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled: If uncontaminated, sweep up or collect, and reuse as product. If contaminated with other materials, collect in suitable containers. Spilled material is very slippery when wet.

7 HANDLING AND STORAGE

Handling Precautions: Steps to be taken in case material is released or spilled: If uncontaminated, sweep up or collect, and

reuse as product. If contaminated with other materials, collect in suitable containers. Minimize

blowdown or other practices that generate high airborne dust concentrations.

Storage Requirements: Store in a cool, dry place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: None required for outdoor mixing and application. Use dust collection system for indoor handling

operations.

Personal Protective Equip: Respiratory Protection: If dust concentrations exceed recommended Permissible Exposure Limits, use

NIOSH- approved dust respirators, with approval TC-21C-xxx, until feasible engineering controls are

completed.

Ventilation: Local exhaust or other ventilation that will reduce dust concentrations to less than

Permissible Exposure Limits is recommended.

Eye Protection: If high dust concentrations exist, tight-fitting goggles are recommended to reduce dust

exposure to the eyes.

Other Protective Equipment: Optional.



GHS Safety Data Sheet PROFILE Products, LLC

Slik Color™

MSDS Number: LIM029 Revision Date: 1/1/14

Page 3 of 4

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Blue green powdery mixture

Physical State: Powder Odor: Slightly aromatic with earthy tone

Vapor Pressure:N.A.Solubility:Very Soluble

Freezing/Melting Pt.: N.A.

10 STABILITY AND REACTIVITY

Stability: Product is stable under all normal conditions.

Conditions to Avoid: Contact with strong acids and oxidizers may generate heat.

Materials to Avoid: Strong acids and oxidizers

Hazardous Polymerization: Will not occur.

1 TOXICOLOGICAL INFORMATION

Inhalation- N.E.

Intravenous- Rat - LD50:15mg/kg Oral - Rat - LD50:3160 mg/kg

12 ECOLOGICAL INFORMATION

3 DISPOSAL CONSIDERATIONS

Can be disposed of in an approved disposal facility, in accordance with applicable federal, state, and local regulations. The nature and extent of contamination, if any, may require use of specialized disposal methods.

14 TRANSPORT INFORMATION

DOT Class: Not regulated #



GHS Safety Data Sheet PROFILE Products, LLC

Slik Color™

MSDS Number: LIM029 Revision Date: 1/1/14

Page 4 of 4

15

REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Silica, crystalline quartz (14808607 1.5-2.5%) MASS, NRC, OSHAWAC, PA, TXAIR

*C.I. Basic Green 4 (569642 <20%) MASS, NJHS, PA, SARA313, TSCA

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
NRC = Nationally Recognized Carcinogens
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance
CSWHS = Clean Water Act Hazardous substances
EHS302 = Extremely Hazardous Substance
EPCRAWPC = EPCRA Water Priority Chemicals
HAP = Hazardous Air Pollutants
NJEHS = NJ Extraordinarily Hazardous Substances
NJHS = NJ Right-to-Know Hazardous Substances
OSHAHTS = OSHA Hazardous and Toxic Substances
OSHAPSM = OSHA Chemicals Requiring process safety management
PROP65 = CA Prop 65
SARA313 = SARA 313 Title III Toxic Chemicals
TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List)
TXHWL = TX Hazardous Waste List

TSCA = Toxic Substances Control Act

OTHER INFORMATION

16