



SlikColorTM



- FORMERLY LABELED AS DYE CRYSTALS
- SUPER HIGH CONCENTRATED MAKER DYE FOR IMPROVED VISUAL METERING
- CONTAINS POLYACRYLAMIDE (PAM) TO ACT AS A HOSE SLICKIFIER
- IMPROVES THE COLOR OF ALL TYPES OF LIGHTLY DYED HYDRAULIC MULCHES
- INCREASES SHOOTING DISTANCE OF HYDRAULIC SLURRY

DIRECTIONS FOR USE

ADD SLIKCOLOR TO THE HYDRAULIC SEEDER WHEN THE TANK IS 1/3 FULL OF WATER. THEN ADD SEED, SOIL AMENDMENTS, FIBER MULCH AND FERTILIZER TO SLURRY. PLEASE REFER TO EQUIPMENT MANUFACTURER'S LOADING INSTRUCTIONS.

PHYSICAL PROPERTIES

VISCOSITY (SAYBOLT)	20 CPS +- 2
SURFACE TENSION	61.2 DYNES / CM
SPECIFIC GRAVITY	1.0783

APPLICATION RATE

HYDRO-SEEDING (IMPROVED COLOR)	1 LB PER 3000 GALLONS OF H2O
STRAW MULCH SEEDING (TACK SLURRY)	2 LBS PER 3000 GALLONS OF H2O

PACKAGING

11 LB JUG, TWO PER CASE, SHIPPED 36 CASES PER 48 x 48 PALLET, ALSO PACKAGED IN 1LB WATER SOLUBLE BAGS, ELEVEN PER CASE



DISTRIBUTED BY