

## SAFETY DATA SHEET

according to 29 CFR 1910.1200 and GHS

Page 1/8

### Prozap® LD-44T

Revision 0  
Revision date 2018-10-08

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

<b>Product name</b>	Prozap® LD-44T
<b>Product code</b>	0073010, 0073011

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Product Use</b>	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC8] Biocidal products (e.g. Disinfectants, pest control);
<b>Description</b>	Aerosol insecticide.

##### 1.3. Details of the supplier of the safety data sheet

<b>Company</b>	Neogen Corporation
<b>Address</b>	620 Leshler Place Lansing MI 48912 USA
<b>Web</b>	www.neogen.com
<b>Telephone</b>	517-372-9200/800-234-5333
<b>Email</b>	regulatorysupport@neogen.com

##### 1.4. Emergency telephone number

<b>Emergency telephone number</b>	1-800-234-5333
-----------------------------------	----------------

##### Further information

<b>Manufactured By:</b>	Chem-Tech Ltd. 1006 Business Highway 5 Pleasantville, IA 50225 U.S.A.
<b>Hotline(s):</b>	Chem-Tech Ltd. is a wholly-owned subsidiary of Neogen Corporation. Medical: United States (1-800-498-5743), International (1-651-523-0318). Spill/CHEMTREC: United States (1-800-424-9300), International (1-703-527-3887).

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

<b>2.1.2. Classification - GHS</b>	: EUH066; Flam. Liq. 3: H226; Eye Irrit. 2: H319; STOT SE 3: H336; Aquatic Chronic 2: H411;
------------------------------------	---

##### 2.2. Label elements

<b>Hazard pictograms</b>	
--------------------------	---

## Prozap® LD-44T

Revision 0  
Revision date 2018-10-08

## 2.2. Label elements

<b>Signal Word</b>	Warning
<b>Hazard Statement</b>	EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 3: H226 - Flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
<b>Precautionary Statement: Prevention</b>	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting// equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
<b>Precautionary Statement: Response</b>	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 - In case of fire: Use media appropriate to the surrounding fire conditions to extinguish. P391 - Collect spillage.
<b>Precautionary Statement: Storage</b>	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.
<b>Precautionary Statement: Disposal</b>	P501 - Dispose of contents/container to an approved waste disposal facility in accordance with local and national regulations.

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

## EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Acetone	606-001-00-8	67-64-1	200-662-2		50 - 60%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;
152A Aerosol propellant		75-37-6			30 - 40%	Liquified gas: H280;
n-Octyl bicycloheptene dicarboximide		113-48-4	204-029-1		1 - 10%	Acute Tox. 3: H311;
Piperonyl butoxide		51-03-6	200-076-7		1 - 10%	Aquatic Acute 1: H400; Aquatic Chronic 1: H410;
Pyrethrins (Pyrethrum)		8003-34-7			0.5 - 1%	Acute Tox. 4: H302+H312+H332; Aquatic Acute 1: H400; Aquatic Chronic 1: H410;

## Further information

The exact percentage (concentration) of composition has been withheld as a trade secret.

## Prozap® LD-44T

Revision 0  
Revision date 2018-10-08**SECTION 4: First aid measures****4.1. Description of first aid measures**

Inhalation	Move the exposed person to fresh air. If breathing stops, provide artificial respiration. If breathing is difficult give oxygen.
Eye contact	Rinse immediately with plenty of water. Contact lenses should be removed.
Skin contact	Wash with soap and water.
Ingestion	If swallowed, seek medical advice immediately and show this container or label.

**4.2. Most important symptoms and effects, both acute and delayed**

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
Eye contact	May cause eye irritation.
Skin contact	May cause irritation to skin.
Ingestion	Ingestion may cause nausea and vomiting.

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

	Use extinguishing media appropriate to the surrounding fire conditions.
--	---

**5.2. Special hazards arising from the substance or mixture**

	Aerosol. Heat will increase pressure in sealed containers.
--	--

**5.3. Advice for firefighters**

	In case of fire and/or explosion do not breathe fumes. Wear suitable respiratory equipment when necessary.
--	--

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

	Adopt best Manual Handling considerations when handling, carrying and dispensing. Wear suitable gloves and eye/face protection.
--	---

**6.2. Environmental precautions**

	Do not empty into drains; dispose of this material and its container in a safe way. Do not flush into surface water.
--	--

**6.3. Methods and material for containment and cleaning up**

	Absorb spillage to prevent material damage. Clean with detergents. Avoid solvents.
--	--

**6.4. Reference to other sections**

	See section 2, 8, and 13 for further information.
--	---

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

	Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact with eyes.
--	--

**7.2. Conditions for safe storage, including any incompatibilities**

	Keep away from sources of ignition - No smoking. Contact with combustible material may cause fire. Heat will increase pressure in sealed containers. Avoid contamination of food or feedstuffs.
--	---

**7.3. Specific end use(s)**

	See section 1.2 for further information.
--	--

## Prozap® LD-44T

Revision 0  
Revision date 2018-10-08**SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

Occupational exposure controls.

## Exposure Limit Values

Acetone	ACGIH TLV TWA: 500	ACGIH TLV STEL: 750
	Notations: A4; BEI	OSHA PEL 8hr TWA ppm: 1000
	OSHA PEL 8hr TWA mg m3: 2400	Skin Designation: -
	NIOSH REL 10hr TWA ppm:	NIOSH REL 10hr TWA mg m3:
	NIOSH REL 15 min ST ppm:	NIOSH REL 15 min ST mg m3:
Pyrethrins (Pyrethrum)	ACGIH TLV TWA: 5 mg/m <sup>3</sup>	ACGIH TLV STEL: -
	Notations: A4	OSHA PEL 8hr TWA ppm: -
	OSHA PEL 8hr TWA mg m3: 5	Skin Designation: -
	NIOSH REL 10hr TWA ppm:	NIOSH REL 10hr TWA mg m3:
	NIOSH REL 15 min ST ppm:	NIOSH REL 15 min ST mg m3:

DNEL: Derived no-effect level.

## Exposure Pattern - Workers

Acetone	Acute inhalation - Systemic effects	2420 mg/m <sup>3</sup>	
	Long-term - inhalation - Systemic effects	1210 mg/m <sup>3</sup>	Long-term - dermal - Systemic effects 186 mg/kg

## Exposure Pattern - General population

Acetone	Long-term - inhalation - Systemic effects	200 mg/m <sup>3</sup>	
	Long-term - dermal - Systemic effects	62 mg/kg	Long-term - oral - Systemic effects 62 mg/kg

## 8.2. Exposure controls

Appropriate engineering controls	Ensure adequate ventilation of the working area.
Individual protection measures	Adopt best Manual Handling considerations when handling, carrying and dispensing. Use appropriate personal protective equipment.
Eye / face protection	Use as appropriate: Safety glasses.
Skin protection - Hand protection	Use as appropriate: Chemical resistant gloves.
Respiratory protection	Do not breathe gas/fumes/vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment.

**SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

## Prozap® LD-44T

Revision 0  
Revision date 2018-10-08

## 9.1. Information on basic physical and chemical properties

<b>State</b>	Aerosol
<b>Color</b>	Clear/Yellow
<b>Odor</b>	Characteristic
<b>Odour threshold</b>	No data available
<b>pH</b>	No data available
<b>Melting point</b>	No data available
<b>Freezing Point</b>	No data available
<b>Boiling point</b>	No data available
<b>Flash point</b>	< 50 °C
<b>Evaporation rate</b>	No data available
<b>Flammability limits</b>	Flame extension: 16"
<b>Vapor pressure</b>	No data available
<b>Vapor density</b>	No data available
<b>Partition coefficient</b>	No data available
<b>Autoignition temperature</b>	No data available
<b>Viscosity</b>	No data available
<b>Explosive properties</b>	No data available
<b>Oxidising properties</b>	No data available
<b>Solubility</b>	Insoluble in water

## 9.2. Other information

<b>Bulk Density</b>	0.653 g/cm <sup>3</sup>
<b>VOC (Volatile organic compounds)</b>	No data available

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

	No data available.
--	--------------------

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## 10.3. Possibility of hazardous reactions

	Avoid contact with: Combustible materials.
--	--

## 10.4. Conditions to avoid

	Avoid sparks, flames, heat and sources of ignition.
--	---

## 10.5. Incompatible materials

	No data available.
--	--------------------

## 10.6. Hazardous decomposition products

	Carbon oxides.
--	----------------

## SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

<b>Acute toxicity</b>	No Significant Hazard.
<b>Skin corrosion/irritation</b>	May cause irritation to skin.
<b>Serious eye damage/irritation</b>	May cause irritation to eyes.

## Prozap® LD-44T

Revision 0  
Revision date 2018-10-08

## 11.1. Information on toxicological effects

Respiratory or skin sensitisation	May cause allergic reactions in susceptible people.
Carcinogenicity	Not found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs, Volumes 1-112. Not listed in the National Toxicology Program (NTP) 13th Report on Carcinogens. Not listed in the OSHA standard 1910.1003 Carcinogens.
Reproductive toxicity	No teratogenic effects reported.
STOT-single exposure	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Aspiration hazard	Potential for aspiration if swallowed.
Repeated or prolonged exposure	Avoid prolonged or repeated exposure.

## 11.1.4. Toxicological information

Acetone	Inhalation Rat LC50/8 h: 50100 mg/m3 Dermal Guinea Pig LD50: 7426 mg/kg	Oral Rat LD50: 5800 mg/kg
Pyrethrins	Oral Rat LD50: 87 mg/kg	Inhalation Rat LC50/4 h: 0.6 mg/l

## SECTION 12: Ecological information

## 12.1. Toxicity

Acetone	Daphnia EC50/48h: 8800.000000 mg/l	Rainbow trout LC50/96h: 5540 mg/l
Pyrethrins	Daphnia EC50/48h: 0.216000 mg/l Rainbow trout LC50/96h: 0.244 mg/l	Algae EC50/72h: 4.9 mg/l

## 12.2. Persistence and degradability

	No data available.
--	--------------------

## 12.3. Bioaccumulative potential

	No data available.
--	--------------------

## Partition coefficient

	Prozap® LD-44T No data available
--	----------------------------------

## SECTION 13: Disposal considerations

## 13.1. Waste treatment methods

	Dispose of contents/container to an approved waste disposal facility in accordance with local and national regulations. Do not burn or incinerate. Follow label instructions.
--	---

## SECTION 14: Transport information

## Hazard pictograms

--	--

## 14.1. UN number

	UN1950
--	--------

## Prozap® LD-44T

Revision 0  
Revision date 2018-10-08

## 14.2. UN proper shipping name

	AEROSOLS
--	----------

## 14.3. Transport hazard class(es)

DOT	2
Subsidiary risk	see SP63
IMDG	2
Subsidiary risk	see SP63
IATA	2
Subsidiary risk	see SP63

## 14.4. Packing group

Packing group	-
---------------	---

## 14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

## DOT

Hazard ID	-
Tunnel Category	(D)

## IMDG

EmS Code	F-D S-U
----------	---------

## SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>Regulations</b>	<p>Hazard Communication Standard: 29 Code of Federal Regulations 1910.1200: Occupational Safety and Health Standards: Z: Toxic and Hazardous Substances: Hazard Communication.</p> <p>All chemicals in this product are TSCA listed or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory. TSCA - United States Toxic Substances Control Act Section 8(b) Inventory.</p> <p>US State Regulations: New Jersey Right-to-Know Hazardous Substance List: Pyrethrins, Piperonyl butoxide</p> <p>Pennsylvania Right-to-Know Hazardous Substance List: Pyrethrins, Piperonyl butoxide, Acetone.</p> <p>Rhode Island Right-to-Know Hazardous Substance List: Pyrethrins, Piperonyl butoxide, Acetone.</p>
--------------------	--

## Inventories

Ingredient	TSCA	MA	SARA313	CALPROP65	CWA307	CAA112	CWA311	SARA302	SARA304
Acetone (2-Propanone)	Y	N	N	N	N	N	N	N	N
Pyrethrins	N	N	N	N	N	N	Y	N	N

## Further information

<b>FIFRA</b>	This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data
--------------	--

## Prozap® LD-44T

Revision 0  
Revision date 2018-10-08

## Further information

FIFRA Signal Word FIFRA Warning	sheets (SDS), and for workplace labels of non-pesticide chemicals. The hazard information required on the pesticide label is reproduced below. The pesticide label also includes other important information, including directions for use.
	CAUTION.
	Hazards to humans and domestic animals. Avoid contact with eyes, skin or clothing. Harmful if swallowed. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

## SECTION 16: Other information

## Other information

Text of Hazard Statements in Section 3	<p>DISCLAIMER: The information and recommendations set forth herein ("Information") are presented in good faith and believed to be correct as of the date issued. No representation is made regarding the completeness or accuracy of the Information. Further, because of the many factors that affect the use of this product, the Information is supplied upon the condition that the person(s) receiving it will make their own determination regarding its suitability for their own unique purpose(s), prior to use.</p> <p>Except as expressly stated herein, NO WARRANTIES, GUARANTEES, OR REPRESENTATIONS OF ANY KIND, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, USAGE OF TRADE, OR RESULTS TO BE OBTAINED BY USE OF THIS PRODUCT are made with respect to this product or use of this product. The product covered is furnished "as is" and only subject to the warranties herein provided, no liability is assumed resulting from the use of this product.</p>
	<p>EUH066 - Repeated exposure may cause skin dryness or cracking.            Flam. Liq. 2: H225 - Highly flammable liquid and vapour.            Eye Irrit. 2: H319 - Causes serious eye irritation.            STOT SE 3: H336 - May cause drowsiness or dizziness.            Liquified gas: H280 - Contains gas under pressure; may explode if heated.            Acute Tox. 3: H311 - Toxic in contact with skin.            Aquatic Acute 1: H400 - Very toxic to aquatic life.            Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.            Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled</p>