

RODENT PROOFING COMPOUND - PROFESSIONAL USE



ROBAN BARRIER™

PHYSICAL STOP BARRIER

+

INSTANTLY WATERPROOF

+

NO PESTICIDES

+

INSTANTLY EFFECTIVE

+

IPM COMPLIANT

+

PATENTED WHEN SET

+

METAL FIBERS REINFORCED

+

METAL DETECTABLE



KEEP OUT OF THE REACH OF CHILDREN.
Not for internal consumption.

PREMIUM PEST BLOCKER

Roban Barrier is an animal friendly barrier pest control paste, reinforced with metal fibers for outstanding protection. It acts as a physical barrier, sealing seams, cracks, and holes to prevent ingress from rodents and other pests. Roban Barrier contains no pesticides, is instantly waterproof and highly effective. All this makes Roban Barrier fully compliant with the Integrated Pest Management (IPM) approach.

APPLICATIONS
Cracked openings, cracks, joints and holes in brickwork, brick walls, siding, sealant cracks, steel, cast iron, PVC, drains, sewage pipes and electrical ducts.

HOW TO USE
Use only as directed. Ensure surface is clean and dry. Openings should be at least 1/8 inch (3 mm) wide for Roban Barrier to achieve proper adhesion. Remove the Roban Barrier cartridge to a caulking gun and cut the nozzle of the cartridge with pliers, scissors or a sharp knife to your desired bead size. Apply Roban Barrier to the area that needs to be sealed, with a depth of at least 1/8 inch (3 mm). Make sure the area is completely filled to the edges on all sides. To finish, smooth the Roban Barrier gently with a wire brush. The required layer depth may vary in order to achieve maximum blocking capacity. Roban Barrier can be installed in cold or warm weather conditions (-50°F / 17.0°F) (-45°C / 75°C). The surface will be dry after 48 hours in normal weather conditions (70°F / 21°C), at which point it can be painted if so desired. Wear gloves for convenience. Wash hands after use. Clean tools with a dry cloth after use. If necessary, use mineral spirits on tools for cleaning. Do not apply near heat sources.

IMPORTANT NOTICE & WARRANTY
To the extent consistent with applicable law, the manufacturer warrants that this product will be free from defects in material and manufacturing for 90 days from the date of purchase from an authorized distributor. As such, the product is non-refundable when used in accordance with the directions for use. This warranty does not extend to the use of Roban Barrier in a manner inconsistent with its labeling or when used under abnormal conditions. Many factors beyond the control of the manufacturer and/or installer within the user's knowledge and control can affect the use and performance of Roban Barrier in a particular application. Given the variety of factors that can affect the use and performance of Roban Barrier, the user is solely responsible for evaluating Roban Barrier and determining whether it is fit for a particular purpose and suitable for the user's method of application. All such risks shall be assumed by the user.

PRECAUTIONARY STATEMENTS
Roban Barrier is not considered to be hazardous under the OSHA HazCom 2012 regulations or the Federal Hazardous Substances Act for consumer products.

Storage: Store product in original container.
Color: Grey
Weight: 11.12 oz. / 313.40 g.

Manufactured for PelGar International Ltd.
PelGar USA
215 Gargreen Ct
Spartanburg, PA 16222
www.pelgar-usa.com
PelGar Asia Pacific
Level 22, 66 Anson Rd
Singapore, SINGAPORE
www.pelgar-asia.com




Roban Barrier™ is a trademark of PelGar International Ltd.