



Precautionary Statements

To the best of our knowledge, RoBan Barrier is not considered to be hazardous under the OSHA HazCom 2012 regulations or the Federal Hazardous Substances Act, for consumer products.



RoBan Barrier™ is a trademark of PelGar International Ltd.

Important notice & Warranty

To the extent consistent with applicable law, PelGar International Ltd. warrants that this product will be free from defects in material and manufacturing for 90 days from the date of purchase from an authorized distributor. In that case, the product is reasonably fit when used in accordance with the directions for use.

This warranty does not extend to the use of RoBan Barrier in a manner inconsistent with its labeling or when used under abnormal conditions. Many factors beyond the control of the manufacturer and/or uniquely within the user's knowledge and control can affect the use and performance of RoBan Barrier in a particular application. Given the variety of factors that can affect the use and performance of RoBan Barrier, the applicator is solely responsible for evaluating RoBan Barrier and determining whether it is fit for a particular purpose and suitable for the user's method of application. All such risks shall be assumed by the user.



Instructions for use



Manufactured for PelGar International Ltd

PelGar USA
Saylorsburg, PA 18353
www.pelgar-usa.com

PelGar Asia Pacific
Brisbane, QLD 4000
www.pelgar.asia



www.pelgar.co.uk

Instructions

Preparation

Make sure the surface is clean and dry. Remove any loose material.

Application

- 1 Cut off the tip of the cartridge and screw on the applicator nozzle
- 2 Cut the applicator nozzle to a desired size depending on the size of the gap
- 3 Place the cartridge into a standard caulking gun
- 4 Slowly pull the caulking gun trigger. Apply evenly around the edges and fill the entire gap or opening
- 5 Smooth with a palette knife if desired
- 6 The barrier is now active
- 7 Clean hands and tools with a dry cloth after use, if necessary use mineral spirits.

Please note

- Keep out of reach of children
- Avoid contact with eyes and mouth
- Not suitable for consumption
- Can be used for openings/ducts of at least 1/4 inch (6 mm).
- Make sure the layer depth is at least 3/4 of an inch (18 mm).
- Do not apply near or around sources of heat
- Can be painted after 48 hours (at 70°F / 21°C)
- Surface is dry after 48 hours (at 70°F / 21°C)
- Store in a frost-free place
- Required layer depth may vary
- Waste resulting from the use of this product may be disposed of on-site or at an approved waste disposal facility

RoBanBarrier: Animal-friendly barrier paste

RoBan Barrier is used to seal seams, cracks and holes in order to prevent ingress from rodents and other pests. RoBan Barrier qualifies for exemption from registration under the Federal Insecticide, Fungicide and Rodenticide Act.

RodentStop applications include:

- Cracks, joints and holes in brickwork.
- Joints and expansion joints.
- Steel, cast-iron and PVC recesses and ducts.
- Settlement cracks.
- Connections between brickwork and drains.
- Sewer connections
- Ducts for (electrical) cables
- Gnawed openings

Advantages of RoBan Barrier:

- Ready-to-use
- Contains no pesticides
- Instantly waterproof (suitable for indoor & outdoor application)
- Instantly active barrier
- Sustainable
- IPM compliant
- Paintable
- Installation possible in cold and warm conditions (-50°F / 170°F) [-45°C / 75°C]
- Metal reinforced and metal detectable
- Exempt from FIFRA registration



Industries

RoBan Barrier's unique properties allow the barrier paste to be used on a wide scale in the food industry as prescribed in the specifications.

RoBan Barrier can be also be used in kitchens, bakeries, distribution centres, manufacturing facilities and companies with hygiene sensitive areas and environmental requirements.

Composition

Blend of vegetable oils, fillers, EPS beads and metal fibers.

Packing

RoBan Barrier is packaged in 340 g (± 12 oz) standard caulking tube cartridges.

A box contains 12 cartridges of 300 ml each.



Disclaimer: to the extent possible the information in this brochure has been compiled with the utmost care. The product is supplied in the state it is actually in and without any (implicit) warranty or guarantee with respect to the soundness and suitability for a particular purpose or use other than those directed by the label. We are not liable for any damage that may result from the use of the information provided in this brochure. For the most up-to-date information on the use of this product, we refer you to our website: www.pelgar.co.uk. Version March 2017.

www.pelgar.co.uk