



SoilCover® Wood

MSDS Number: CON006

Revision Date: 1/1/14

Page 1 of 5

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

PROFILE Products, LLC
750 LAKE COOK ROAD
SUITE 440
BUFFALO GROVE, IL 60089

Phone: (847) 215-1144
Fax: (847) 215-0577
Email: profileproducts.com
Web: www.profileproducts.com

Product Name: SoilCover® Wood
Revision Date: 1/1/14
MSDS Number: CON006
CAS Number: Not applicable
Product Use: Erosion control mulch for revegetation and hydraulic seeding

Product Description: Green dyed wood fibers

2

HAZARDS IDENTIFICATION

Route of Entry: Inhalation, skin contact, eye contact


Inhalation: Wood dust may cause sneezing, irritation, and dryness of the nose and throat. Dust may aggravate pre-existing respiratory conditions.

Skin Contact: Wood dust can cause irritation. Skin absorption is not known to occur.

Eye Contact: Wood dust can irritate the eyes.

Ingestion: No reports of human ingestion.

NFPA: Health = 1, Fire = 1, Reactivity = 0



OSHA Classification: Wood dust is a hazardous substance as defined by the Hazard Communication Standard 29CFR 1910.1200



SoilCover® Wood

MSDS Number: CON006

Revision Date: 1/1/14

Page 2 of 5

3

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Perc.	Chemical Name

4

FIRST AID MEASURES

Inhalation: Usually not a problem. Remove to fresh air if respiratory irritation develops, and get medical aid promptly if irritation persists.

Skin Contact: Usually not a problem. Wash off with running water if irritation is experienced.

Eye Contact: Open eyelids and flush with water.

Ingestion: Get medical attention.

5

FIRE FIGHTING MEASURES

Flammability: Combustible product

Flash Point: Not applicable

Flash Point Method: Not applicable

Autoignition Temp: 200-260°C (400-500°F)

Conditions to avoid: In contact with flames or hot surfaces

Flammable- Extinguish with water; same as a wood fire

6

ACCIDENTAL RELEASE MEASURES

Scoop up product. Wear goggles and respirator if dust is produced in unventilated areas. Wet product will be slippery.

7

HANDLING AND STORAGE

Handling Precautions: Clean up areas where dust settles. Minimize blowdown or other practices that generate high airborne dust concentrations.

Storage Requirements: Store in a cool, dry place. Keep away from sources of ignition.



SoilCover® Wood

MSDS Number: CON006

Revision Date: 1/1/14

Page 3 of 5

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: None required for outdoor mixing and application. Use dust collection system for indoor handling operations.

Personal Protective Equip: Eye Protection: Wear goggles when emptying bags and during other operations where there is a risk of dust entering the eyes.
Gloves: Leather, plastic or rubber gloves could be worn to minimize skin irritation.
Respirators: When handling methods generate dust at concentrations that exceed occupational exposure limits, wear a NIOSH approved respirator. A fabric respirator or a facepiece respirator with dust cartridges will generally provide adequate protection.
Footwear: The product is slippery when wet. Wear appropriate footwear.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Dyed, green wood fibers - Pine and mixed hardwoods		
Physical State:	Wood Fibers	Odor:	Mild wood odor
Spec Grav./Density:	Lighter than water		
Vapor Pressure:	N/A		

10 STABILITY AND REACTIVITY

Stability: Stable product

Conditions to Avoid: Contact with strong acids and oxidizers may generate heat. Product may ignite at temperatures in excess of 200°C (400°F).

Materials to Avoid: Strong acids and oxidizers

Hazardous Polymerization: Will not occur.

11 TOXICOLOGICAL INFORMATION

EFFECTS OF CHRONIC EXPOSURE:

Inhalation: Frequent and repeated exposure to wood dust is associated with an increased risk of developing nasal cancer.
Skin Contact: Although rare, wood dust may cause dermatitis in sensitized people.

Occupational Exposure Limits:

Wood dusts- All other species: ACGIH (2007): TLV-TWA 1 mg/m³ (Inhalable fraction); A4

Particulates Not Otherwise Regulated (PNOR): OSHA: PEL-TWA 15 mg/m³ (Total Dust); 5 mg/m³ (Respirable fraction)

Irritancy: Wood dust is a mild irritant

Sensitization: Some wood dusts may cause allergic skin reactions



SoilCover® Wood

MSDS Number: CON006

Revision Date: 1/1/14

Page 4 of 5

12

ECOLOGICAL INFORMATION

48-hr LC₅₀ = >100% for Daphnia magna when runoff generated using ASTM D7101 (2"/hr rainfall rate) was tested according to EPA-821-R-02-012.

13

DISPOSAL CONSIDERATIONS

Normally can be disposed of as a wood residue. Ensure disposal is in compliance with local, provincial (state), and federal regulations.

14

TRANSPORT INFORMATION

DOT Class: Not regulated #

15

REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
NRC = Nationally Recognized Carcinogens
OSHA WAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance
CSWHS = Clean Water Act Hazardous Substances
EHS302 = Extremely Hazardous Substance
EPCRAWPC = EPCRA Water Priority Chemicals
HAP = Hazardous Air Pollutants
NJ EHS = NJ Extraordinarily Hazardous Substances
NJHS = NJ Right-to-Know Hazardous Substances
OSHA PSM = OSHA Chemicals Requiring Process Safety Management
SARA 313 = SARA 313 Title III Toxic Chemicals



GHS Safety Data Sheet

PROFILE Products, LLC

SoilCover® Wood

MSDS Number: CON006

Revision Date: 1/1/14

Page 5 of 5

16	OTHER INFORMATION
----	--------------------------