

SPECIFICATIONS

ELECTRICAL	110V / 120V	
WATER CAPACITY	1.85 GAL	7L
OPERATING PRESSURE	87 PSI	6 BAR
WATTAGE	1750W	
BOILER TEMPERATURE	302°F - 320°F	150 °C - 160 °C
TIP TEMPERATURE	250°F	121°C
TANK CONSTRUCTION	Stainless steel 18/10	
LENGTH OF ELECTRICAL CORD	15.4'	4.7 m
LENGTH OF STEAM HOSE	9.6'	2.95 m
NET WEIGHT	23 lb	10.5 kg
SHIPPING WEIGHT	31 lb	14 kg
PRODUCT DIMENSIONS	19" x 14.5" x 14"	48 x 37 x 35.5 cm
SHIPPING DIMENSIONS	23" x 20.5" x 16"	58.5 x 52 x 4 cm
COUNTRY OF ORIGIN	Italy	
ELECTRICAL APPROVAL	cETLus	
WARRANTY	Limited 1 year, Lifetime Tank	

TANDEM PRO 2000CV

COMMERCIAL STEAM CLEANER WITH CSS AND WET AND DRY VACUUM CLEANER

The Tandem Pro is a multi-use cleaning unit. It functions as a steam cleaner and steam extractor as well as a wet/dry vacuum. The Tandem Pro is an ideal chemical-free alternative for cleaning and sanitizing all surfaces encountered in commercial cleaning settings yet has the option of using a non-toxic degreasing detergent, making it the ultimate commercial cleaning machine.

Steam deodorizes and sanitizes with heat and moisture. Steam in conjunction with the vacuum function allows the Tandem Pro to reduce time associated with steaming alone and waste materials like paper towels and cleaning cloths. The Tandem Pro implements leading edge technology and accessories designed for cleaning professionals.

EMBRACE THE POWER OF STEAM



STEAM AND DEGREASER VOLUME CONTROL



WET/DRY VACUUM



MADE IN ITALY



BOILER TANK
LIFETIME WARRANTY



6 BAR PRESSURE



CSS TECHNOLOGY



EMC2



KILLS GERMS



TANDEM PRO 2000CV

COMMERCIAL STEAM CLEANER WITH CSS AND WET AND DRY VACUUM CLEANER





