

PRODUCT INFORMATION

| | |
|---------------|--------------|
| NAME | Typhoon 3™ |
| MODEL NUMBER | FZVAAK-3 |
| MSRP | \$337.49 |
| UPC / BARCODE | 850020839629 |



PRODUCT IMAGE



DESCRIPTION

Now introducing the 4-Gallon Typhoon Series 3 Sprayer! With a 30-ft spray distance, this sprayer introduces design updates that significantly improve your spraying experience. By taking our customers feedback, we've implemented various tank advancements and brand new nozzle lineups.

To view the most updated operation guide visit: www.fzspray.com/operation-guides or scan the QR code



WHAT'S INCLUDED

| | PART NUMBER | PART NUMBER |
|---------------------------|-------------|-----------------------------|
| 18V/5.2 Ah LI-ION BATTERY | FZAAEM | UV-RESISTANT 5-FT PVC HOSE |
| 21V/2.5A BATTERY CHARGER | FZAAEL | FZRAOF |
| STAINLESS-STEEL WAND | FZRAAS | ADJUSTABLE CONE NOZZLE |
| SPRAY GUN | FZRABV | FZAA0L |
| COMFORTSTRAPS™ | FZAAGD | 0° PIN STREAM TEEJET NOZZLE |
| | | FZAA0K |
| | | 45° FAN TEEJET NOZZLE |
| | | FZAAANM |

LOGISTICAL INFORMATION

| | | | |
|--------------------|--------------------|-----------------|------------|
| GROSS / NET WEIGHT | 16 / 14 pounds | PALLET QUANTITY | 36 units |
| PACKAGE SIZE | 14" x 9.5" x 21.7" | 20' GP QUANTITY | 420 units |
| WEIGHT PER UNIT | 16 lbs | 40' GP QUANTITY | 840 units |
| WEIGHT PER PALLET | 627 lbs | 40' HQ QUANTITY | 1080 units |

PRODUCT SPECIFICATIONS

| | | | | | |
|------------------------|---------------------------------------|--|----------------------------|---|-----------------------------|
| TANK TYPE | 4-Gallon Backpack | | GUN / WAND TYPE | Pressure Washer Spray Gun with Viton™ Seal / Quick-Connect Stainless Steel Wand | |
| PUMP TYPE | High Pressure Diaphragm Pump (LR) | | BATTERY VOLTAGE/CAPACITY | 18V / 5.2Ah | |
| WORKING PRESSURE | Low Speed (open flow) 8 psi | High Speed (dead head) 115 psi | BATTERY CELL TYPE | Lithium Ion | |
| SEAL TYPE | Viton™ | | CHARGER TYPE | 21V / 1A | |
| FLOW RATE | Low Speed (open flow) .42 GPM | High Speed (open flow) 1.12 GPM | CHARGE TIME | ~2 hours | |
| LIQUID OUTPUT / CHARGE | Low Speed (open flow) > 110 gal | High Speed (open flow) > 110 gal | BATTERY CYCLE LIFE | 1,000 Charge Cycles | |
| SPRAY DISTANCE | > 30 Feet (10 Meters) | | CONTINUOUS WORKING TIME | Low Speed > 180 minutes | High Speed > 120 minutes |
| | | | AGENCY/STANDARDS APPROVALS | UL / CE / RoHS | |