

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard.
 29CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List) STICKY STRIPS - STICKY BOARDS	<i>Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.</i>
--	---

Section I

Manufacturer's Name OLSON PRODUCTS, INC.	Emergency Telephone Number (330) 723-3210
Address (Number, Street, City, State and ZIP Code) P.O. BOX 1043 MEDINA, OHIO 44258	Telephone Number for Information (330) 723-3210
	Date Prepared 08/26/02
	Signature of Preparer (optional)

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
NONE ARE CONSIDERED HAZARDOUS.				

Section III – Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H2O = 1)	0.912
Vapor Pressure (mm Hg.)	N/A	Melting Point	N/A
Vapor Density (Air = 1)	N/A	Evaporation Point (Butyl Acetate = 1)	N/A
Solubility in water INSOLUBLE			
Appearance and odor LIGHT YELLOW TRANSPARENT SOLID; NEGLIGIBLE ODOR			

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) GREATER THAN 400°F; SETA-FLASH CLOSED TESTER	Flammable Limits INSIGNIFICANT	LEL N/A	UEL N/A
Extinguishing Media CO2; DRY CHEMICAL; FOAM			
Special Fire Fighting Procedures FIREFIGHTERS SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS TO PROTECT AGAINST POTENTIALLY TOXIC AND IRRITATING FUMES.			
Unusual Fire and Explosion Hazards COMBUSTION MAY RELEASE NOXIOUS OR TOXIC VAPORS.			

Section V – Recovery Data

Stability	Unstable		Conditions to Avoid
	Stable	x	N/A

Incompatibility (Materials to Avoid)

NONE KNOWN

Hazardous Decomposition or Byproducts

CARBON MONOXIDE, CARBON DIOXIDE, UNKNOWN HYDROCARBONS

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	x	

Section VI – Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	YES	YES	

Health Hazards (Acute and Chronic)

NEGLEGIBLE, BELOW 250 DEGREES F. OTHER THAN THERMAL HAZARDS
 ABOVE 120 DEGREES F.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO

Signs and Symptoms of Exposure

N/A

Medical Conditiona

Generally Aggravated by Exposure NONE

Emergency and First Aid Procedures

NONE REQUIRED. STICKY ADHESIVE MAY BE REMOVED WITH VEGETABLE
 OIL.

Section VII – Precautions for Safe Handling and Use**Steps to Be Taken in Case Material is Released or Spilled**

AT TEMPERATURES BELOW 120° F PICK UP THE PRODUCT. ABOVE 120°F USE THERMAL
 PROTECTION WHEN PICKING UP PRODUCT.

Waste Disposal Methods

IN ACCORDANCE WITH EXISTING FEDERAL, STATE & LOCAL ENVIRONMENTAL REGULATIONS.

Precautions to Be Taken in Handling and Storage

STORE IN A COOL, DRY AREA.

Other Precautions**Section VIII – Control Measures****Respiratory Protection (Specify Type)**

NONE BELOW 250°F.

Ventilation	Local Exhaust	NONE BELOW 250°F.	Special	NONE
	Mechanical (General)	NONE BELOW 250°F.	Other	NONE

Protective Gloves

WHEN ABOVE 120°F.

Eye Protection

NONE

Other Protective Clothing or Equipment

NONE

Work/Hygenic Practices

USUAL